



Order #: 150737

Order Name: West Coast Spec Stock

Order Revision #: 0

Dealer/Customer: CENTRAL VALLEY TRAILER REPAIR (FRESNO,CA)  
Contact: CENTRAL VALLEY TRAILER REPAIR (FRESNO,CA)  
Sales Person: Ernest Lopez

Date: 12/16/2015  
Requested Date: 7/1/2016  
Dealer/Branch P.O: n/a  
Customer #: 90411  
Customer P.O: n/a

itm	Product	Reference #	Name	Model #	Qty
1	ESS - Everest Super Seal Reefer	C-15204	Copy of West Coast Spec	ESS-1114-31053	70

Line Item 1

Configuration Reference #: C-15204

Configuration Name: Copy of West Coast Spec

FG Item: 17216xxxx

Product: ESS - Everest Super Seal Reefer

Model #: ESS-1114-31053

Mode of Transportation: Customer Pick-Up

Product

Product ESS - Everest Super Seal Reefer  
Manufacturing Plant Wayne, NE

Geometric Dimensions

Packaged Options None  
Serial Plate U.S.Certification Plate  
Overall Height 13' 6"  
Overall Length 53' 0"  
Overall Width 102.36"  
Upper Coupler Height 47"  
Kingpin Location 36.00"  
Landing Gear Location 105.0" From Kingpin  
Wedge No Wedge  
Undercarriage Design Tandem Axle, Slide Air- Ride Suspension, 49" Axle Centers  
Miscellaneous Text None

Front



<b>Front Corner Type</b>	6" Radius
<b>Front Corner Sheet</b>	Stainless Steel 0.021"
<b>Front Sheets</b>	Aluminum, 0.040"
<b>Front Upright</b>	Zee, Aluminum, 1.63"
<b>Front Vents</b>	None
<b>Quantity and Type of Front Vent</b>	None
<b>Vent Screens</b>	None
<b>Location of Front Vent</b>	None
<b>Tracking System (Customer Furnished)</b>	None
<b>Electrical Connector and Gladhand Location</b>	Offset Roadside, Overlaid
<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Red / Blue Urethane Seals
<b>Document Holder</b>	Great Dane Standard with Logo At Roadside Front
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Miscellaneous Text</b>	None
<b>Side Exterior and Structural</b>	
<b>Side Sheet Material</b>	Aluminum, 0.040"
<b>Side Sheet Texture</b>	Corrugated
<b>Side Post Type</b>	Jay, Aluminum 1.13"
<b>Side Post Spacing</b>	8/16/24" Centers
<b>Bottom Rail Fasteners</b>	0.38" Aluminum Rivets
<b>Rub Rail Type</b>	None
<b>Rub Rail Location</b>	None
<b>External Protection Package (Lift Pads)</b>	None
<b>Miscellaneous Text</b>	None
<b>Rear</b>	
<b>Rear Frame Type</b>	Stainless Steel Swing Door Frame
<b>Header Type</b>	4" Header
<b>Rear Bumpers</b>	Rubber Dock Bumper
<b>Bars Between Buckplate Lamps</b>	Install Stainless Steel Vertical Bars Between Each Tail Lamp
<b>Rear Impact Guard</b>	Carbon Steel Rear Impact Guard, Bolt On Vertical, Weld On Horizontal
<b>Rear Access System</b>	Handhold Roadside Door (CUSTOMER REQUIRES Intermediate Channel)
<b>Tag Bracket Location</b>	Standard
<b>License Plate Installation</b>	None
<b>Miscellaneous Text</b>	None
<b>Rear Doors</b>	
<b>Rear Door Type</b>	Frame Type Swing With Triple Seal Gasket And Stainless Steel Diamond Pattern Finish Cover Sheet



<b>Lockrod</b>	1 Per Door
<b>Hinge per Door</b>	5 Per Rear Door
<b>Rear Door Holdback</b>	Standard
<b>Floor-Door Jamb</b>	Standard
<b>Type of Scuffband on Rear Door</b>	Aluminum, 0.188" Smooth 16"
<b>Rear Door Scuffband Location</b>	Installed at Bottom of Swing Door
<b>Rear Door Scuffband Position</b>	Overlaid on Swing Door
<b>Inside Safety Release</b>	Without Inside Safety Release
<b>Rear Door Vent</b>	One Swing Vent 5" X 15" Opening
<b>Rear Vent Location</b>	Lower Curbside
<b>Rear Door Vent Screen</b>	With Screen
<b>Hazardous Placard</b>	None
<b>Haz. Mat. Placard Location</b>	None
<b>ERC Switch (Rear)</b>	None
<b>Miscellaneous Text</b>	None

#### Roof Options

<b>Roof Bows</b>	1.13" Roof Bows on 32" Centers
<b>Roof Sheet</b>	Aluminum
<b>Miscellaneous Text</b>	None

#### Floor

<b>Type of Floor</b>	Alum Duct 1.38" Smooth
<b>Front And Rear Floor Gutter</b>	Install Front Gutters And Front Drains, Install Rear Gutters And Rear Drains
<b>Reefer Rear Threshold / Dockplates</b>	(5) Smooth Aluminum Dock Plates Over Rear Gutter
<b>Reefer Floor Inserts</b>	44" Long Inserts in Center 72" of Floor
<b>Miscellaneous Text</b>	None

#### Lining / Scuffband

<b>Side Lining</b>	0.070" ThermoGuard
<b>Front Lining</b>	0.070" ThermoGuard
<b>Ceiling Lining</b>	0.070" ThermoGuard
<b>Rear Door Lining</b>	0.070" ThermoGuard
<b>Unit Numbers on Lining</b>	None
<b>Rows of Front Scuffband</b>	None
<b>Rows of Side Scuffband</b>	1 Row
<b>Quantity of Rows of Logistic track</b>	None
<b>Miscellaneous Text</b>	None

#### Scuff/Logistic Track

<b>Type of Side Scuffband (Row One)</b>	16" High Integral Extruded Aluminum
<b>Scuffband Location (Row One)</b>	Installed at Floor Level



<b>Side Scuffband Position (Row One)</b>	Recessed on Sidewall
<b>Miscellaneous Text</b>	None
<b>Understructure</b>	
<b>Upper Coupler Type</b>	4.25" Channel
<b>Bottom Plate Thickness</b>	0.25"
<b>Approach Plate</b>	0.19" Tapered With Stn Stl Rolled Lip
<b>Landing Gear</b>	GD60
<b>Landing Gear Foot / Shoe Type</b>	10" X 10" Cushion Foot
<b>Landing Gear Bracing</b>	Channel Type
<b>Special Landing Gear Wing Plate</b>	Carbon steel mounting plates
<b>Landing Gear Handle Location</b>	Roadside
<b>Landing Gear Lube System</b>	No Special Lube System
<b>Tire Carrier</b>	None
<b>Crossmembers Ahead of Landing Gear</b>	Aluminum Hat Type on 12" Centers
<b>Front Tire Protector Plates</b>	None
<b>Crossmembers Over Landing Gear</b>	4" Steel I-Beam on 12" Centers
<b>Bay Area Crossmembers</b>	5" Aluminum I-Beam on 12" Centers
<b>URG Crossmembers</b>	4" Steel I-Beam on 12" Centers
<b>Extra Crossmembers at Rear</b>	8" centers Last 4' of Body (1 extra typical)
<b>Extra URG Rail Length</b>	Add 2'
<b>Rear Tire Protector Plates</b>	None
<b>Aerodynamic Fairings - Side Skirts</b>	Strehl Trailer Blade Side Skirt
<b>Miscellaneous Text</b>	None
<b>Suspension</b>	
<b>Model of Suspension</b>	Hendrickson ULTRAAK 40K
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Locking Mechanism</b>	Air-Assist Pin Release
<b>Dump Valve</b>	Surelok Feature
<b>Pintle Hook</b>	None
<b>Miscellaneous Text</b>	None
<b>Rear Ramps and Mud Flaps</b>	
<b>Mudflaps</b>	Great Dane, Smooth Black with Logo
<b>Mudflap Quantity/Bracket Material</b>	1-Pair
<b>Mudflap Mounting Location</b>	On Undercarriage
<b>Miscellaneous Text</b>	None
<b>Brakes and Wheel Ends</b>	
<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke



<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Stemco Automatic Slack 5.50"
<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	None
<b>Tire-Inflation-System/Tire/Wheel Options</b>	Hendrickson TIREMAAX PRO
<b>Tire Inflation System Pressure</b>	Great Dane Standard Pressure Setting
<b>Wheel Seals</b>	Platinum-Plus Performance Package
<b>Axle Spindle Nuts</b>	Pro-Torq Spindle Nut
<b>Hubcaps</b>	Hubcap To Accommodate Tire Inflation System
<b>Wheel Lubricant</b>	Oil
<b>Anti-Lock Brakes</b>	Wabco 2S/1M Easy Stop
<b>ECU Monitored Option</b>	None
<b>Optional Diagnostic Cable</b>	None
<b>Brake Valves</b>	Great Dane Standard
<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text</b>	None

**Tires / Wheels / Hubs and Drums**

---

<b>Rim/Disc Wheel Size</b>	22.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
<b>Brake Drum Balancing</b>	Supplied Balanced Only
<b>Wheel Type</b>	22.5" Steel Disc Wheels With Aluminum Disc Wheels Outboard, Hub Piloted
<b>Wheel/Rim Vendor</b>	Great Dane Steel/Great Dane Aluminum
<b>Wheel Stud Options</b>	Long Studs for Future Alum Wheels
<b>Wheel Spacer (Corrosion Barrier)</b>	Spacer between Inner and Outer Disc Wheels
<b>Tire Size</b>	295/75R 22.5
<b>Tire Brand</b>	Bridgestone Ecopia R197 (G)
<b>Spare Tire</b>	None
<b>Miscellaneous Text</b>	None

**Electrical**

---

<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Solid Pin
<b>Front Top Rail Lights Loc</b>	1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement)
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	3 Each Side, Stop/Tail/Red Turn
<b>Stainless Theft-Resistant Flange for LED Lamps</b>	Installed on Buckplate lamps with Stainless Rivets



<b>Rear Header Light Locations</b>	Center Cluster of 3 with 1 Each Side Outboard Corner, Dual Intensity Brake Indication
<b>Top and Bottom Side Marker Lamps/ Location</b>	5 Each Side Top and Bottom Rail Evenly Spaced
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Install Below Bottom rail
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Filler Plate Size</b>	None
<b>Miscellaneous Text</b>	None
<b>Electrical Interior</b>	
<b>Dome Light Quantity</b>	None
<b>Dome Light Vendor/Type</b>	None
<b>Dome Light Location Width-wise</b>	None
<b>Dome Light Location Length-wise</b>	None
<b>Mounting Position Reference Points</b>	None
<b>Domelight Switch Qty / Type / Loc</b>	None
<b>Miscellaneous Text</b>	None
<b>Finish/Paint/Decal</b>	
<b>Front Finish, Front Corner Sheet</b>	Stainless Steel
<b>Front Finish</b>	Pre-Painted White
<b>Side Finish</b>	Pre-Painted White
<b>Rivet Color</b>	Unpainted
<b>Top Rail Paint</b>	None
<b>Bottom Rail Paint</b>	None
<b>Rear Frame Finish</b>	None (Stainless Steel)
<b>Rear Door Finish</b>	Stainless Steel
<b>Undercarriage Finish</b>	Black Undercoat
<b>Wheel Finish</b>	White Steel, Standard Polish Aluminum Outboard
<b>Upper Coupler Finish</b>	Great Dane Standard Coating
<b>Landing Gear Finish</b>	Finish to Match Undercarriage
<b>Upper Running Gear Finish</b>	Great Dane Standard Coating
<b>Conspicuity Treatment Location</b>	Great Dane on Bottom Rail
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Unit Numbers (Exterior)</b>	None



Miscellaneous Text	None
<b>Insulation</b>	
Front Insulation	3.50" Urethane
Side Insulation	2.00" Urethane
Roof Insulation	3.00" Urethane
Rear Door Insulation	3.00" Urethane
Floor Insulation	2.50" Urethane
Subfloor Type	0.040" ThermoGuard
Floor Sills	Composite
Miscellaneous Text	None
<b>Controlled Temperature Unit</b>	
Preparation for Nose Mounted Unit	030 No Unit Installation, Brace and Cut Hatch
Type of Nose Mounted Unit	Thermo King Precedent (Large Opening)
Unit Position	Standard
Quantity of Ceiling Evaporators	None
Miscellaneous Text	None
<b>Controlled Temperature Accessories</b>	
Fuel Tank Capacity	None
Fuel Tank Location	None
Battery	None
Refrigeration Remote Indicator Lights	None
Refrigeration Unit Duct And Transition	None
Remote Control Panel	None
Miscellaneous Text	None
<b>Bulkheads, Air Return</b>	
Bulkhead/Air Return	None
Factory Furnished Pallet Stops Air Return	None
Center Partitions and Preparation	None
Miscellaneous Text	None
<b>Side Door Type/Location</b>	
Quantity of Side Doors	0
<b>Rear</b>	
Liftgate Preparation	None
<b>Rear Ramps and Mud Flaps</b>	
Walkramp at Rear	None

